

HIGHLIGHTS

- ✓ Affordable reference probe
- ✓ Accuracy ± 0.015 °C at 0.01 °C
- ✓ Temperature range: -200 °C to 670 °C
- ✓ Customized dimensions available



OVERVIEW

AM1750 Secondary Reference PRT provides our customers an affordable reference probe for precision temperature measurement and calibration. This PRT features accuracy of ± 0.015 °C at 0.01°C and short term stability of ± 0.007 °C. Two different lengths of PRTs are available at 12-inch and 20-inch.

The sensing element is designed to protect the platinum sensing wire from contamination at high temperatures, giving the device a high level of stability and repeatability in performance. A uniquely designed support structure and filling material provides excellent balance between the hysteresis effect, mechanical shock and thermal shock performance. This high performance probe fully meets ITS-90 criteria for reference thermometers.

FEATURES

- Temperature range: -200 °C to 670 °C
- Accuracy: ± 0.015 °C at 0.01°C
- Long term drift: ± 0.01 °C
- Short term stability: 0.007 °C
- Durable and shock resistance
- Temperature Coefficient 0.003925 $\Omega/^\circ\text{C}$
- $W(\text{Ga}) \geq 1.11807$
- Inconeltm sheath
- Customized dimensions available

SPECIFICATIONS

Temperature Range	1750-12: -200°C to 670°C 1750-20: -200°C to 670°C
Resistance at 0 °C	Nominal 100 Ω
Temperature Coefficient	0.003925 Ω/ Ω/°C
Accuracy	±0.025°C at -196 °C ±0.015°C at 0.01 °C ±0.035°C at 420 °C ±0.05°C at 660 °C
Drift	±0.01°C at 0 °C after 100 hours at 660 °C
Short Term Stability	±0.007°C
Thermal Shock	±0.005°C after 10 times thermal cycles from minimum to maximum temperatures
Hysteresis	<=0.005°C
Self-heating	50 mW/°C
Response Time	9 seconds for 63% response to step change in water moving at 3 feet per second
Measurement Current	0.5 mA or 1 mA
Sensor Length	32 mm
Sensor Location	5 mm from tip
Insulation Resistance	>1000 MΩ at room temperature
Sheath Material	Inconel™
Dimension	1750-12: 0.25 inch X 12 inch (6.35 mm X 305 mm) 1750-20: 0.25 inch X 20 inch (6.35 mm X 500 mm)
External Leads	Teflon™ –insulated copper wire, 4 leads, 2.5 meters
Handle Dimension	15mm (OD) X 65 mm (L)
Handle Temperature Range*	-50°C to 180°C
Calibration Options	Optional: NIST Traceable Calibration and Data Ordering Model for Calibrations: 5007

*Handle temperature outside this range will cause damage to the probe.

OPTIONAL ACCESSORIES

Model	Description
9001	Wooden Carrying Case for 1750-12
9002	Wooden Carrying Case for 1750-20