

Blackbox 130 datasheet

mA version



Blackbox is Pulsar's compact non-contacting ultrasonic level measurement range, designed to fit right into a distributed control system. A small control unit sits remotely on your site that connects to a dB ultrasonic transducer. Simple does not mean unsophisticated – the Blackbox range enjoys the benefit of advanced DATEM echo processing for a reliable, consistent result.



Blackbox 130 – General	
Power Supply:	115V AC +5%/-10%, 50/60 Hz, 10-28V DC
Approvals:	UL/CuL NEMA 4X (IP65)
Temperature:	Ambient -4 to 131°F (-20 to 55°C)
...model with keypad and display	
Function:	Level and Volume
Display:	Back lit, 2 x 12 alpha numeric
Programming:	Easy descriptive menu driven parameters via Integral keypad, handheld programmer or Blackbox PC software
...model without keypad and display	
Function:	Level
Programming:	Easy descriptive menu driven parameters via handheld programmer or Blackbox PC
Outputs	
Relays:	2, form "C" (SPDT) relays rated 2A at 115V/240V AC
Relay Functions:	Level alarms, basic on/off control, device failed
Analogue Outputs:	4-20mA isolated or non-isolated
Analogue Output Functions:	Level, Distance, Space or (Volume on keypad & display model only)
Echo Processing	
Echo Processing:	Digital echo processing
Masking:	DATEM Obstruction Masking (unique intelligent masking technology, continually adapting to prevent false levels being shown)
Options	
Enclosure:	Keypad & display
Software:	Blackbox PC - Diagnostic software, parameters accessible and echo traces viewable
Compatible Transducers	
Level / Volume App. :	dB3, dB6, dB6, dB10, dB15, dB25, dB40
Please see related transducer datasheet for specifications and options.	

