



## Electronic Transmitter Pressure, Level, and Vacuum

*PT/EL TH Series*



- Nema 4X Anodized Alum. Terminal Head
- $\pm 0.25\%$  FS Accuracy
- Ranges 5"WC-300 psig, Vacuum & Absolute
- 4-20 mA, 2-wire output
- FM And CSA Approved, 3A Sanitary



**PMC Electronic Pressure Transmitters** accurately measure pressure, level, and vacuum in processes where clogging of the diaphragm face is a particular concern. The small, 1½" diameter of the transmitter allows installation flush with the inside wall of pipes 3" in diameter and larger. This feature eliminates the usual pocketing problems encountered with conventional flange-mounted and recessed-diaphragm transmitters. PMC incorporates a high-precision ceramic capacitive pressure sensor to ensure accuracy and durability. This type of sensor is ideally suited for high-wear applications. **The PT/EL Series** of transmitters provides overpressure protection of up to 10 times the full scale range. The Nema 4X rated, Anodized Aluminum Terminal Junction Head provides a flexible solution for connection to the transmitter and can be configured with a Local LCD Display. Access to the terminal strip is provided through a convenient latched, flip-up top. Cables enter the Terminal Junction Head via a ½"-14 NPT threaded port. The optional ½" Nylon Gland Nut provides a liquid-tight cord connection.

**3A Sanitary version (SAN)** provides your choice of certified sanitary process connections including weld-on nipple, NPT threaded nipple, or Tri-Clamp. **Double Ring version (DR)** provides your choice of process connections including weld-on nipple, or NPT threaded nipple. See the Process Connections Data sheet for a detailed list and description of options.

\*FM & CSA approved for use in hazardous locations, Class I,II,III, Division1, Groups A,B,C,D,E,F, & G rated.

***Pneumatically Operated Transmitters Also Available***

*Precision Solutions for pressure, level, vacuum and humidity measurement*

## STANDARD SPECIFICATIONS

### Full Scale Ranges

0 - 5"WC to 0 - 300 psi gauge  
 ± 5"WC to ± 400" WC Compound  
 0 - 3" Hg to 0 - 30" Hg Vacuum  
 0 - 15 psi to 0 - 150 psi absolute

Ranges below 40"WC, absolute ranges, and/or compound ranges available with ceramic diaphragm only

### Static Accuracy

± 0.25% of Full Scale  
 Combined non-linearity, hysteresis, and repeatability

### Overpressure

10X for Full Scale Ranges up to 100 psi  
 4X for Full Scale Ranges over 100 psi

### Compensated Temperature Range

-4°F to 175°F (-20°C to 80°C)

### Operating Temperature Range

Ambient: -40°F to 175°F (-40°C to 80°C)  
 Process: -40°F to 250°F (-40°C to 125°C)

### Temperature Effects

Thermal Zero Shift: ±0.0075%/°C  
 Thermal Span Shift:  
 ± 0.003%/°C for ranges < 6 psi  
 ± 0.005%/°C for ranges 6 psi and above

### Electrical

Output: 2-wire, 4-20 mA  
 Supply Voltage: 24 VDC nominal supply

### Zero Setting

± 5% FS, potentiometer adjustment

### Span Setting

± 15% FS, potentiometer adjustment

### Housing

Nema 4X, EMI / RFI protected, Anodized Aluminum Construction

PMC adopts a continuous development program which sometimes necessitates specification changes without notice.

## ORDERING INFORMATION

### PT/EL TH Series Electronic Transmitter Pressure, Level, and Vacuum

When ordering please specify the following:

MODEL PMC - PT/EL	
SAN	Sanitary version
DR	Double Ring version
Range	Specify psi, "WC, Bar, absolute, gauge, etc.
Diaphragm	
Ha	Havar
Hc	Hastelloy C
Ta	Tantalum
Cer	Ceramic
Termination	
TH	Terminal Head
TH/D	Adds Display

(1) Select (2) Specify (3) Select (4) Select


#### Order Code Example: PMC-PT/EL-DR-100"WC-Hc-TH/D

- (1) Model: PMC-PT/EL-DR
- (2) Range: 100" WC
- (3) Diaphragm Material: Hastelloy C
- (4) Electrical Termination: Terminal Head with LCD Display

## OPTIONS

- Remote Electronics
- Gland Nut Cable Connection
- LCD Display
- Submersible Versions
- Process Connections  
 Sanitary, Flush-Mount, Tri-Clamp, Flange and Threaded Process Connections available

Contact PMC for other options and accessories



All measurements shown in inches

HEAD OFFICE



### Process Measurement & Controls, Inc.

11 Old Sugar Hollow Road  
 Danbury, CT 06810 U.S.A.  
 Tel: 203-792-8686  
 Fax: 203-743-2051  
 Email: sales@pmc1.com  
[www.pmc1.com](http://www.pmc1.com)

Represented By: